



Programming(SLCS) Manual

TX / DX/ DL / XD / XQ / XL Series

SRP-770III, E770III, XT Series

Ver. 2.01

Table of Contents

| | |
|---|-----------|
| 1. Introduction of Manual | 4 |
| 1-2 Information for calculating position on image buffer..... | 6 |
| 1-3 Command List..... | 8 |
| 1-4 Programming Considerations | 10 |
| 2. Detail Description | 11 |
| 2-1 Commands for Designing a Label..... | 11 |
| 2-1-1 T (Text String) | 12 |
| 2-1-2 V (Text String Vector Font) | 15 |
| 2-1-3 B1 (1 Dimensional Barcode)..... | 18 |
| 2-1-4 B2 (2 Dimensional Barcode)..... | 21 |
| 2-1-5 B3 (Special Barcode)..... | 30 |
| 2-1-6 BD (Block Draw) | 35 |
| 2-1-7 CD (Circle Draw) | 38 |
| 2-1-8 CS (Character Set selection)..... | 39 |
| 2-1-9 P (Print) | 42 |
| 2-2 Media Buffer Related Commands..... | 44 |
| 2-2-1 ST (Set Printing Type) | 45 |
| 2-2-2 SM (Set Margin) | 45 |
| 2-2-3 SF (Set Back-Feed Option) | 47 |
| 2-2-4 SL (Set Length) | 48 |
| 2-2-5 SW (Set Width)..... | 51 |
| 2-2-6 CB (Clear Buffer) | 52 |
| 2-2-7 CL (Calibration Length setting) | 52 |
| 2-3 Printer Setting Commands..... | 53 |
| 2-3-1 SS (Set Speed)..... | 54 |
| 2-3-2 SD (Set Density)..... | 54 |
| 2-3-3 SO (Set Orientation) | 55 |
| 2-3-4 SP (Set Port) | 56 |
| 2-3-5 SA (Set Offset)..... | 57 |
| 2-3-6 TA (Tear-off/Cutter Position Setting) | 57 |
| 2-4 Variable Related Commands | 58 |
| 2-4-1 SC (Set Counter) | 59 |
| 2-4-2 AC (Auto Counter) | 60 |
| 2-4-3 SV (Set Variable) | 61 |
| 2-4-4 ? (Get Variables)..... | 62 |
| 2-4-5 PV (Print with Variables) | 63 |
| 2-5 Template Related Commands..... | 64 |
| 2-5-1 TS (Template store Start)..... | 65 |
| 2-5-2 TE (Template store End)..... | 65 |
| 2-5-3 TR (Template Recall) | 66 |
| 2-5-4 TD (Template Delete) | 67 |
| 2-5-5 TI (Template Information)..... | 67 |
| 2-5-6 TN (Template Name) | 68 |
| 2-5-7 TT (Template Transfer) | 68 |
| 2-6 Image Related Commands | 69 |
| 2-6-1 IS (Image Store) | 70 |
| 2-6-2 IR (Image Recall)..... | 70 |
| 2-6-3 ID (Image Delete) | 71 |

| | |
|---|-----------|
| 2-6-4 II (Image Information) | 71 |
| 2-6-5 LD | 72 |
| 2-6-6 LC | 74 |
| 2-6-7 BMP | 76 |
| 2-7 Downloadable font Related Commands | 77 |
| 2-7-1 DT (Download True Type Font) | 78 |
| 2-7-2 DD (Downloaded font Delete) | 79 |
| 2-7-3 DI (Downloaded font Information) | 80 |
| 2-8 The Others | 81 |
| 2-8-1 @ (Initialize Printer) | 81 |
| 2-8-2 PI (Printer Information) | 81 |
| 2-8-3 CUT (Auto-cutter Enable/Disable) | 82 |
| 2-8-4 ^cp (Check Printer Status and Report 2 bytes) | 83 |
| 2-8-5 ^cu (Check Printer Status and Report 1 byte) | 84 |
| 2-8-6 ^PI (Send Printer information to host) | 85 |
| 3. Programming Example | 86 |
| 3-1 Example) T_resident | 86 |
| 3-2 Example) T_Rotate4 | 87 |
| 3-3 Example) V_resident | 88 |
| 3-4 Example) V_Rotate4 | 89 |
| 3-5 Example) Code39 | 90 |
| 3-6 Example) BD1 | 91 |
| 3-7 Example) BD3 | 92 |
| 3-8 Example) BD4 | 94 |
| 3-9 Example) BD5 | 95 |
| 3-10 Example) Slope | 96 |
| 3-11 Example) SW&SL | 97 |
| 3-12 Example) TEST00_TS | 99 |
| 3-13 Example) TEST00_TR | 100 |
| 3-14 Example) TEST04_TS | 101 |
| 3-15 Example) TEST04_TR | 102 |
| 3-16 Example) IR1 | 102 |
| 3-17 Example) TEST10_TS | 103 |
| 3-18 Example) TEST10_TR | 103 |
| 3-19 Example) TEST11_TS | 104 |
| 3-20 Example) TEST11_TR | 104 |
| 3-21 Example) SAMPLE LABEL | 105 |

1. Introduction of Manual

In this chapter, the basic concept of SLCS and some information necessary for the programmer to use SLCS will be explained. Please read this part before starting programming for efficient and easy use of BIXOLON Label Printer.

We at BIXOLON maintain ongoing efforts to enhance and upgrade the functions and quality of all our products. In following, product specifications and/or user manual content may be changed without prior notice.

1-1 Image Buffer Configuration

1) Maximum size


A) When Using Double Buffering Function

832dots × 1216dots (104mm × 152mm) = 4 inch × 6 inch

B) When using Single Buffering Function

832dots × 2432dots (104mm × 304mm) = 4 inch × 12 inch

2) Dot size : 0.125mm(W) × 0.125mm(H) (203dpi)



1-2 Information for calculating position on image buffer


1) Relation between position and number of dots

| Inch | mm | dots | Resolution |
|------|-------|------|------------|
| 0.04 | 1 | 8 | 203 dpi |
| 0.40 | 10.00 | 80 | |
| 1.00 | 25.40 | 203 | |
| 1.25 | 31.75 | 254 | |
| 1.50 | 38.10 | 305 | |
| 1.75 | 44.45 | 355 | |
| 2.00 | 50.80 | 406 | |
| 2.25 | 57.15 | 457 | |
| 2.50 | 63.50 | 508 | |
| 2.75 | 69.85 | 556 | |
| 3.00 | 76.20 | 610 | |
| 4.00 | 101.6 | 813 | |


2) Font Information

| Font name | Width x Height (dots) |
|-------------|-----------------------|
| 0 | 09 x15 |
| 1 | 12 x 20 |
| 2 | 16 x 25 |
| 3 | 19 x 30 |
| 4 | 24 x 38 |
| 5 | 32 x 50 |
| 6 | 48 x 76 |
| 7 | 22 x 34 |
| 8 | 28 x 44 |
| 9 | 37 x 58 |
| Korean a | 16 x 16(ascii:9x15) |
| Korean b | 24 x 24(ascii:12x24) |
| Korean c | 20 x 20(ascii:12x20) |
| Korean d | 26 x 26(ascii:16x30) |
| Korean e | 20 x 26(ascii:16x30) |
| Korean f | 38 x 38(ascii:22x34) |
| GB2312 m | 24 x 24(ascii:12x24) |
| BIG5 n | 24 x 24(ascii:12x24) |
| Shift JIS j | 24 x 24(ascii:12x24) |
| Vector | Scalable |

3) Example of text and barcode



4) Example of rotation



1-3 Command List


| Command | Description | Remarks | Page |
|---|-------------------------|---|------|
| 1. Commands for Designing Label | | | |
| T | Text | Draw text string on the image buffer | |
| V | Text (Vector Font) | Draw vector text string on the image buffer | |
| B1 | 1D barcode | Draw 1D Barcode on the image buffer | |
| B2 | 2D barcode | Draw 2D Barcode on the image buffer | |
| B3 | Special barcode | Draw special barcode on the image buffer | |
| BD | Block Draw | Draw line or box on the image buffer | |
| CD | Circle Draw | Draw circle on the image buffer | |
| CS | Character Set selection | Select international code table | |
| P | Print | Start printing the content of image buffer | |
| | | | |
| 2. Media & Buffer related Commands | | | |
| ST | Set Print Type | Select Thermal Direct / Transfer printing | |
| SM | Set Margin | Set the marginal value of the image buffer | |
| SF | Set Back-feed Option | Set back-feeding option | |
| SL | Set Label Length | Set length of label | |
| SW | Set Label Width | Set length of label | |
| CB | Clear Buffer | Clear image buffer | |
| CL | Set Calibration Length | Set Calibration Length in mm unit | |
| | | | |
| 3. Printer Setting Commands | | | |
| SS | Set Speed | Set printing speed | |
| SD | Set Density | Set printing density from level 0 to 20 | |
| SO | Set Orientation | Set printing direction | |
| SP | Set serial Port | Set serial port configurations | |
| SA | Set Offset | Set offset value | |
| TA | Set Tear-off/Cut | Set Tear-off/Cut value | |
| | | | |
| 4. Variable related Commands | | | |
| SC | Set Counter | Used in Template sequence | |
| AC | Set Counter | Used in normal mode | |
| SV | Set Variable | Used in Template sequence | |
| ? | Get variables | Get content of variables and counters | |
| PV | Print with Variable | Use this command in Template | |

| Command | Description | Remarks | Page |
|--|-------------------------------|---|------|
| 5. Template Related Commands | | | |
| TS | Template store Start | All contents between these commands are saved in printer memory | |
| TE | Template store End | | |
| TR | Template Recall | Load and reuse the stored Template | |
| TD | Template Delete | Delete stored Template from printer memory | |
| TI | Template Information | Print the list of currently stored Templates | |
| TN | Return Template List | Printer sends Template list to HOST | |
| TT | Return Saved Template | Printer sends specific Template contents to HOST | |
| | | | |
| 6. Image Data Related Commands | | | |
| IS | Image Store | PCX format image file can be stored | |
| IR | Image Recall | Load and reuse the stored image | |
| ID | Image Delete | Delete stored image | |
| II | Image Information | Print the list of currently stored images | |
| LD | Bitmap data draw | Draw bitmap image data on the image buffer | |
| LC | Compression bitmap data draw | Draw compression bitmap image data on specific position of image buffer | |
| BMP | BMP format file draw | Draw BMP format file on the image buffer | |
| | | | |
| 7. Downloadable Font Related Commands | | | |
| DT | Download True Type font | Windows system font used | |
| DD | Downloadable font Delete | Delete downloaded font | |
| DI | Downloadable font Information | Print the list of currently stored images | |
| | | | |
| 8. The Others | | | |
| @ | Reset printer | Initialize the printer | |
| PI | Printer Information | Print current setting of printer | |
| CUT | Enable/Disable Cutter option | Cutting is executed after Printing is finished if cutting option is enabled by this command | |
| ^cp | Check Printer Status | Return 2 bytes status values to host | |
| ^cu | Check Printer Status | Return 1 byte status value to host | |
| ^PI | Send Printer information | Send various information to host | |

1-4 Programming Considerations

1) All commands are case-sensitive and some commands require one or more parameters and 'Data'

2) Command Conventions



3) Each command line must be terminated with a 'CR'(0Dh, 13) + 'LF'(0Ah, 10).

4) The commands which draw text, barcode, lines... just draw on the image buffer, they do not start printing



Caution

The 'P' command must be terminated by 'CR'(0x0d). If not, the printer will not start printing until 'CR' comes.

2. Detail Description

2-1 Commands for Designing a Label

These commands are used to design a label by providing text, barcode, line, box... and to print content of image buffer on media.

1) T

Draw **Text String** on the image buffer.

2) V

Draw **Text (Vector Font) String** on the image buffer.

3) B1

Draw **1D Barcode** on the image buffer.

4) B2

Draw **2D Barcode** on the image buffer.

5) B3

Draw **Special Barcode** on the image buffer.

6) BD

Draw **Line, Block, Box & Slope** on the image buffer.

7) CD

Draw **Circle** on the image buffer.

8) CS

Set Code page and ICS(International Character Set).

9) P

Start printing the content of the image buffer.

2-1-1 T (Text String)

Description

Draw text string on the image buffer

Syntax

Tp1,p2,p3,p4,p5,p6,p7,p8,p9,(p10),'DATA'

Parameters

p1 : Horizontal position (X) [dot]

p2 : Vertical position [dot]

p3 : Font selection

| Value | Font Size(pt) | Width × Height(dots) |
|-------|---------------|-----------------------|
| 0 | 6 | 9 × 15 |
| 1 | 8 | 12 × 20 |
| 2 | 10 | 16 × 25 |
| 3 | 12 | 19 × 30 |
| 4 | 15 | 24 × 38 |
| 5 | 20 | 32 × 50 |
| 6 | 30 | 48 × 76 |
| 7 | 14 | 22 × 34 |
| 8 | 18 | 28 × 44 |
| 9 | 24 | 37 × 58 |
| a | KOREAN 1 | 16 × 16 (ascii 9×15) |
| b | KOREAN 2 | 24 × 24 (ascii 12×24) |
| c | KOREAN 3 | 20 × 20 (ascii 12×20) |
| d | KOREAN 4 | 26 × 26 (ascii 16×30) |
| e | KOREAN 5 | 20 × 26 (ascii 16×30) |
| f | KOREAN 6 | 38 × 38 (ascii 22×34) |
| m | GB2312 | 24 × 24 (ascii 12×24) |
| n | BIG5 | 24 × 24 (ascii 12×24) |
| j | Shift JIS | 24 × 24 (ascii 12×24) |

* A to Z are assigned to Downloadable font. Refer to **DT** command.

p4 : Horizontal multiplier : 1 ~ 4

p5 : Vertical multiplier : 1 ~ 4

p6 : Right-side character spacing [dot]

Plus(+) / Minus(-) option can be used. Ex) 5, +3, -10...

p7 : Rotation

| Value | Rotation |
|-------|-------------|
| 0 | No Rotation |
| 1 | 90 degrees |
| 2 | 180 degrees |
| 3 | 270 degrees |

p8 : Reverse printing

N : Normal printing

R : Reverse printing

p9 : Bold

N : Normal

B : Bold

p10 : Text Alignment(Optional)

F : p1 means the position of the first character in text string - **Left alignment**

L : p1 means the position of the last character in text string - **Right alignment**

R: Write text sting form right to left

(BIXOLON → NOLOXIB)

'DATA' : The various data types can be used in the data field as followings.

- 1) Fixed text string : ' Text String'
 - 2) Variables declared in template by **SV** command : **Vnn**
 - 3) Counters declared by the **SC** command : **Cn**
- * 1), 2) and 3) can be mixed together**

Example

```
T50,100,3,1,1,0,0,N,N,'BIXOLON Label Printer'  
T50,100,3,1,1,0,0,N,N,'Manufacturer :'V00  
T50,100,3,1,1,0,0,N,N,V00  
T50,100,3,1,1,0,0,N,N,'Manufacturer :'C0  
T50,100,3,1,1,0,0,N,N,C0
```

*** If you want to print ' or \ then you must type like \' or \\.**

Example

```
SM20,20  
T26,20,0,0,0,0,N,N,'Font- 6 pt'  
T26,49,1,0,0,0,N,N,'Font - 8 pt'  
T26,81,2,0,0,0,N,N,'Font - 10 pt'  
T26,117,3,0,0,0,N,N,'Font - 12 pt'  
T26,156,4,0,0,0,N,N,'Font - 15 pt'  
T26,200,5,0,0,0,N,N,'Font - 20 pt'  
T26,252,6,0,0,0,N,N,'Font - 30 pt'
```

P1

Result

Font – 6 pt
Font – 8 pt
Font – 10 pt
Font – 12 pt

Font – 15 pt

Font – 20 pt

Font – 30 pt

2-1-2 V (Text String Vector Font)

Description

Draw text (Vector Font) string on the image buffer

Syntax

Vp1,p2,p3,p4,p5,p6,p7,p8,p9,p10,p11,p12, 'DATA'

Parameters

p1 : Horizontal position (X) [dot]

p2 : Vertical position (Y) [dot]

p3 : Font selection

U: ASCII (1Byte code)

K: KS5601 (2Byte code)

B: BIG5 (2Byte code)

G: GB2312 (2Byte code)

J: Shift-JIS (2Byte code)

a: OCR-A (1Byte code)

b: OCR-B (1Byte code)

p4 : Font width (W)[dot]

p5 : Font height (H)[dot]

p6 : Right-side character spacing [dot]

Plus (+)/Minus (-) option can be used. Ex) 5, +3, -10...

P7 : Bold

N : Normal

B : Bold

p8 : Reverse printing

N: Normal printing

R: Reverse printing

P9 : Text style

N: Normal

I: Italic

P10 : Rotation

| Value | Rotation |
|-------|-------------|
| 0 | No Rotation |
| 1 | 90 degrees |
| 2 | 180 degrees |
| 3 | 270 degrees |

p11 : Text Alignment (Optional)

L: p1 means the position of the first character in the text string - **Left alignment**

R: p1 means the position of the last character in the text string - **Right alignment**

C: p1 means the position of the center character in the text string - **Center alignment**

P12: Text string write direction

0: Write text string form left to right (BIXOLON)

1: Write text string form right to left (NOLOXIB)

'DATA' : The various data types can be used in the data field as follows.

- 1) Fixed text string: 'Text String'
 - 2) Variables declared in template by **SV** command: **Vnn**
 - 3) Counters declared by the **SC** command: **Cn**
- * 1), 2), and 3) can be mixed together.**

Example

```
V50,100,U,25,25,+1,N,N,N,0,L,0,'BIXOLON Label Printer'  
V50,200,U,35,35,-1,N,N,N,0,L,0, 'Manufacturer :' V00  
V50,300,U,35,35,+1,B,R,I,0,L,0, V00  
V50,400,U,45,25,+1,N,N,N,0,L,0,'Vector Font Test' C0  
V50,500,U,25,45,+1,N,N,N,0,L,0, C0
```

*** If you want to print ' or \ then you must type like ' or \.**

Example

```
V50,100,U,25,25,+1,N,N,N,0,L,0,'Vector Font Test'  
V50,200,U,35,35,-1,N,N,N,0,L,0,'Vector Font Test'  
V50,300,U,35,35,+1,B,R,I,0,L,0,'Vector Font Test '  
V50,400,U,45,25,+1,N,N,N,0,L,0,'Vector Font Test'  
V50,500,U,25,45,+1,N,N,N,0,L,0,'Vector Font Test'  
V50,700,U,65,65,+1,N,N,N,0,L,0,'ABCDEFGHIJKLMNO'  
V50,900,U,65,65,+1,N,N,N,0,L,0,'abcdefghijklmno'  
P1
```

Result

Vector Font Test

Vector Font Test

Vector Font Test

Vector Font Test

Vector Font Test

ABCDEFGHIJKLMNO

abcdefghijklmno

2-1-3 B1 (1 Dimensional Barcode)

Description

Draw 1D Barcode on the image buffer

Syntax

B1p1,p2,p3,p4,p5,p6,p7,p8,(p9),'DATA'

Parameters

p1 : Horizontal position (X) [dot]

p2 : Vertical position (Y) [dot]

p3 : Barcode selection

| p3 | Barcode | p3 | Barcode |
|-----------|------------------|-----------|--------------------|
| 0 | Code39 | 9 | UCC/EAN128 |
| 1 | Code128 | 10 | Code11 |
| 2 | Interleaved 2of5 | 11 | Planet |
| 3 | Codabar | 12 | Industrial 2of5 |
| 4 | Code93 | 13 | Standard 2of5 |
| 5 | UPC-A | 14 | Logmars |
| 6 | UPC-E | 15 | UPC/EAN Extensions |
| 7 | EAN13 | 16 | Postnet |
| 8 | EAN8 | | |

p4 : Narrow bar width [dot]

p5 : Wide bar width [dot]

p6 : Bar code height [dot]

p7 : Rotation

| Value | Rotation |
|-------|-------------|
| 0 | No Rotation |
| 1 | 90 degrees |
| 2 | 180 degrees |
| 3 | 270 degrees |

p8 : HRI (Human Readable Interpretation)

0 : Not printed

1 : Below the bar code(Font Size : 1)

2 : Above the bar code(Font Size : 1)

3 : Below the bar code(Font Size : 2)

4 : Above the bar code(Font Size : 2)

5 : Below the bar code(Font Size : 3)

6 : Above the bar code(Font Size : 3)

7 : Below the bar code(Font Size : 4)

8 : Above the bar code(Font Size : 4)

(p9) : quiet zone width(optional) : 0 ~ 20

- ♣ Quiet zone is added to the front and end of the barcode for safe scanning.
Because of the quiet zone, the barcode seems to be seen drawn in incorrect position. If p9 is not used, the printer automatically sets parameter to 0.

Quiet zone width = p9 × narrow bar width (p4)

‘DATA’ : The various data types can be used in the data field as followings.

- 1) Fixed text string : ‘ Text String’
- 2) Variable declared in template by **SV** command : **Vnn**
- 3) Counter declared by the **SC** command : **Cn**
- 4) In the Code 128, when send data to printer if codeset selection commands (>A,>B,>C) will be used codeset can be selected.

By using **>A**, Codeset will be set Codeset A.

By using **>B**, Codeset will be set Codeset B.

By using **>C**, Codeset will be set Codeset C.

If Codeset select command is not used, automatically set to Auto-mode.

- ♣ 1) , 2) and 3) can be used together

Example

```
B178,196,0,2,6,100,0,0,'1234567890'  
B178,196,0,2,6,100,0,0,V00  
B178,196,0,2,6,100,0,0,C0  
B178,196,1,2,6,100,0,0,'>A1234567890'  
B178,196,1,2,6,100,0,0,'>B1234567890'  
B178,196,1,2,6,100,0,0,'>C1234567890>A5'
```

Example

SM20,20


B178,196,0,2,6,100,0,0,'1234567890'

// Caution: The position is not (178,196) but
(78,196)

B150,468,0,4,10,200,0,0,'1234567890'

P1

Result



2-1-4 B2 (2 Dimensional Barcode)

Description

Draw 2D Barcode on the image buffer

Syntax

B2p1,p2,p3.....'DATA'

Parameters

p1 : Horizontal position (X) [dot]

p2 : Vertical position (Y) [dot]

p3 : 2D barcode selection

| p3 | 2D Barcode |
|-----------|-------------------|
| M | MaxiCode |
| P | PDF417 |
| Q | QR Code |
| D | Data Matrix |
| A | Aztec |
| F | Code 49 |
| C | CODABLOCK |
| B | Micro-PDF |

◆◆ Following parameters (p4, p5 ,Data) are barcodes-specific.

See the following pages for details of each 2D barcodes.

Maxicode(p3 = M)

p1 : Horizontal position (X) [dot]

p2 : Vertical position (Y) [dot]

p3 : M (means 'Maxicode')

p4 : Mode selection

| p4 | Rotation |
|-----------|-----------------|
| 0 | Mode0 |
| 2 | Mode2 |
| 3 | Mode3 |
| 4 | Mode4 |

'DATA' : Data format is dependent on 'Mode'

| Mode | Data Format |
|-------------|--------------------|
| 0 | |
| 2 or 3 | 'cl,co,pc,lpm' |
| 4 | 'lpm' |

cl : Class Code(3 digits)

co : Country Code(3digits)

Mode2 : Numeric Characters

Mode3 : International Characters

pc : Postal Code

lpm : Low priority message(data)

Example

1)Mode 0

B2200,200,M,0,'999,840,06810,7317,THIS IS A TEST OF MODE 0 STRUCTURED CARRIER MESSAGE ENCODING. THIS IS AN 84 CHAR MSG'

2)Mode 2

B2200,200,M,2,'999,840,06810,7317,THIS IS A TEST OF BIXOLON LABEL PRINTER XT5-40. MODE 2 ENCODING. THIS IS AN 84 CHAR.'

3)Mode3

B2200,200,M,3,'999,056,B1050,7317,THIS IS A TEST OF BIXOLON LABEL PRINTER XT5-40. MODE 3 ENCODING. THIS IS AN 84 CHAR.'

4)Mode4

B2200,200,M,4,'THIS IS A 93 CHARACTER CODE SET A MESSAGE THAT FILLS A MODE 4, UNAPPENDED, MAXICODE SYMBOL...'

PDF417(p3 = P)

- p1** : Horizontal position (X) [dot]
- p2** : Vertical position (Y) [dot]
- p3** : P (means 'PDF417')
- p4** : Maximum Row Count : 3 ~ 90
- p5** : Maximum Column Count : 1 ~ 30
- p6** : Error Correction level

| p6 | EC Level | EC Codeword |
|-----------|-----------------|--------------------|
| 0 | 0 | 2 |
| 1 | 1 | 4 |
| 2 | 2 | 8 |
| 3 | 3 | 16 |
| 4 | 4 | 32 |
| 5 | 5 | 64 |
| 6 | 6 | 128 |
| 7 | 7 | 256 |
| 8 | 8 | 512 |

- p7** : Data compression method

| p7 | Data Type | Compression |
|-----------|------------------|------------------------------|
| 0 | Text | 2 Characters per codeword |
| 1 | Numeric | 2.93 Characters per codeword |
| 2 | Binary | 1.2 Bytes per codeword |

- p8** : HRI

- 0 : Not Printed
- 1 : Below the barcode
- p9** : Barcode origin point
 - 0 : Center of barcode
 - 1 : Upper left corner of barcode(default)
- p10** : Module Width : 2 ~ 9
- p11** : Bar Height : 4 ~ 99
- p12** : Rotation

| Value | Rotation |
|--------------|-----------------|
| 0 | No Rotation |
| 1 | 90 degrees |
| 2 | 180 degrees |
| 3 | 270 degrees |

'DATA' : ASCII data or Binary data.

Example

| | |
|--|--------------------------------|
| B2100,750,P,30,5,0,0,1,1,3,10,0,' BIXOLON Label Printer XT5-40' | // (p1,p2) is (100,750) |
|--|--------------------------------|

QR Code(p3 = Q)

p1 : Horizontal position (X) [dot]

p2 : Vertical position (Y) [dot]

p3 : Q (means 'QR Code')

p4 : MODEL selection

1 : MODEL1

2 : MODEL2

p5 : ECC Level

| p6 | Recovery Rate |
|-----------|----------------------|
| L | 7% |
| M | 15% |
| Q | 25% |
| H | 30% |

p6 : Barcode Size : 1~4

p7 : Rotation

| Value | Rotation |
|--------------|-----------------|
| 0 | No Rotation |
| 1 | 90 degrees |
| 2 | 180 degrees |
| 3 | 270 degrees |

'DATA' : ASCII data or Binary data.

Example

B2200,100,Q,2,M,4,0,'ABCDEFGHIJKLMN1234567890' // (p1,p2) is (200,100)

Data Matrix(p3 = D)

p1 : Horizontal position (X) [dot]

p2 : Vertical position (Y) [dot]

p3 : D (the ECC 200 data quality format)

p4 : Barcode Size : 1 ~ 4;

P5 : Reverse

N: Normal

R: Reverse(or Inverse) – Reverse Video or Negative image

(P6) : Rotation

| Value | Rotation |
|--------------|-----------------|
| 0 | No Rotation |
| 1 | 90 degrees |
| 2 | 180 degrees |
| 3 | 270 degrees |

'DATA' : ASCII data or Binary data.

Example

B2200,100,D,2,N,'BIXOLON Label Printer' // (p1,p2) is (200,100)

Aztec Barcode(p3 = A)

p1 : Horizontal position (X) [dot]

p2 : Vertical position (Y) [dot]

p3 : A (means 'Aztec Bar Code')

p4 : Barcode Size: 1~10

p5 : Extended channel interpretation code

0: Disable Extended channel interpretation code

1: Enable Extended channel interpretation code

p6 : Error control and symbol size/type

| Value | Error control and symbol size/type |
|-----------|------------------------------------|
| 0 | Default error correction level |
| 1 ~ 99 | Error correction percentage |
| 101 ~ 104 | 1 ~ 4 layer compact symbol |
| 201 ~ 232 | 1 ~ 32 layer full range symbol |
| 300 | Simple Aztec "Rune" |

p7 : Menu symbol

0 : Disable Menu symbol

1 : Enable Menu symbol

p8 : Number of symbols for structured append : 1 ~ 26

p9 : Optional ID field for structured append : ID field string (Maximum 24 character)

p10 : Rotation

| Value | Rotation |
|-------|-------------|
| 0 | No Rotation |
| 1 | 90 degrees |
| 2 | 180 degrees |
| 3 | 270 degrees |

'DATA' : ASCII data or Binary data.

Example

```
B2100,100,A,5,0,0,0,1,1,0,'THIS IS AZTEC BARCODE TESTTHIS IS AZTEC BARCODE TEST'  
B2400,100,A,7,0,0,0,1,1,1,'THIS IS AZTEC BARCODE TESTTHIS IS AZTEC BARCODE TEST'  
P1
```

Code 49 Barcode(p3 = F)

p1 : Horizontal position (X) [dot]

p2 : Vertical position (Y) [dot]

p3 : F (means 'Code 49 barcode')

p4 : Narrow bar width [dot]

p5 : Wide bar width [dot]

p6 : Barcode height [dot]

p7 : HRI

0 : Not Printed

1 : Below the barcode

2 : Above the barcode

p8 : Starting mode

| Value | Mode |
|-------|------------------------------|
| 0 | Regular Alphanumeric Mode |
| 1 | Multiple Read Alphanumeric |
| 2 | Regular Numeric Mode |
| 3 | Group Alphanumeric Mode |
| 4 | Regular Alphanumeric Shift 1 |
| 5 | Regular Alphanumeric Shift 2 |
| 7 | Automatic Mode |

p9 : Rotation

| Value | Rotation |
|-------|-------------|
| 0 | No Rotation |
| 1 | 90 degrees |
| 2 | 180 degrees |
| 3 | 270 degrees |

'DATA' : ASCII data or Binary data.

Example

B2100,100,F,2,7,22,1,7,0,'12345ABC'

B2300,200,F,2,7,44,2,7,0,'12345ABC'

B2500,300,F,2,7,66,1,7,0,'12345ABC'

B2100,400,F,1,3,88,0,7,0,'12345ABC'

P1

CODABLOCK Barcode(p3 = C)

p1 : Horizontal position (X) [dot]

p2 : Vertical position (Y) [dot]

p3 : C (means 'CODABLOCK barcode')

p4 : Narrow bar width [dot]

p5 : Wide bar width [dot]

p6 : Barcode height [dot]

p7 : Security level

0: Disable

1: Enable

p8 : Number of characters per row (data columns): 2~62

p9 : Mode

| Value | Description |
|-------|---|
| A | CODABLOCK A mode uses the Code 39 character set |
| E | CODABLOCK E mode uses the Code 128 character set |
| F | CODABLOCK F mode uses the Code 128 character set and Automatically adds Function 1.(FNC1) |

p 10 : Number of rows to encode

| Mode | Value |
|------|--------|
| A | 1 ~ 18 |
| E | 2 ~ 4 |
| F | 2 ~ 4 |

p 11 : Rotation

| Value | Rotation |
|-------|-------------|
| 0 | No Rotation |

'DATA' : ASCII data or Binary data.

Example

B210,100,C,2,5,30,0,30,F,4,0,'BIXOLON BARCODE TEST 123BIXOLON BARCODE TEST 123BIXOLON BARCODE TEST 123BIXOLON BARCODE TEST 123'

B210,400,C,2,5,30,0,30,E,4,0,'BIXOLON BARCODE TEST 123BIXOLON BARCODE TEST 123BIXOLON BARCODE TEST 123BIXOLON BARCODE TEST 123'

B210,600,C,2,6,10,0,10,A,18,0,'123'

P1

Micro-PDF417 Barcode(p3 = B)

p1 : Horizontal position (X) [dot]

p2 : Vertical position (Y) [dot]

p3 : B (means 'Micro-PDF417 barcode')

p4 : **Module width : 2 ~8**

p5 : Barcode height [dot] : 1 ~ 99

p6 : **Mode : 0 ~ 33**

(Refer to Micro-PDF417 Mode Table on next page)

p7 : Rotation

| Value | Rotation |
|-------|-------------|
| 0 | No Rotation |
| 1 | 90 degrees |
| 2 | 180 degrees |
| 3 | 270 degrees |

'DATA' : ASCII data or Binary data.

Example

```
B2100,100,B,2,3,12,0,'ABCDEFGHIJKLMN1234567890'
```

```
B2100,300,B,2,3,20,0,'ABCDEFGHIJKLMN1234567890'
```

```
B2100,600,B,4,4,16,0,'ABCDEFGHIJKLMN1234567890'
```

```
B2100,900,B,2,6,8,0,'ABCDEFGHIJKLMN1234567890'
```

P1

******* Mirco-PDF417 Mode Table *******

| Mode (M) | Number of Data Columns | Number of Data Rows | % of Cws for EC | Max Alpha Characters | Max Digits | Remarks |
|----------|------------------------|---------------------|-----------------|----------------------|------------|---------|
| 0 | 1 | 11 | 64 | 6 | 8 | |
| 1 | 1 | 14 | 50 | 12 | 17 | |
| 2 | 1 | 17 | 41 | 18 | 26 | |
| 3 | 1 | 20 | 40 | 22 | 32 | |
| 4 | 1 | 24 | 33 | 30 | 44 | |
| 5 | 1 | 28 | 29 | 38 | 55 | |
| 6 | 2 | 8 | 50 | 14 | 20 | |
| 7 | 2 | 11 | 41 | 24 | 35 | |
| 8 | 2 | 14 | 32 | 36 | 52 | |
| 9 | 2 | 17 | 29 | 46 | 67 | |
| 10 | 2 | 20 | 28 | 56 | 82 | |
| 11 | 2 | 23 | 28 | 64 | 93 | |
| 12 | 2 | 26 | 29 | 72 | 105 | |
| 13 | 3 | 6 | 67 | 10 | 14 | |
| 14 | 3 | 8 | 58 | 18 | 26 | |
| 15 | 3 | 10 | 53 | 26 | 38 | |
| 16 | 3 | 12 | 50 | 34 | 49 | |
| 17 | 3 | 15 | 47 | 46 | 67 | |
| 18 | 3 | 20 | 43 | 66 | 96 | |
| 19 | 3 | 26 | 41 | 90 | 132 | |
| 20 | 3 | 32 | 40 | 114 | 167 | |
| 21 | 3 | 38 | 39 | 138 | 202 | |
| 22 | 3 | 44 | 38 | 162 | 237 | |
| 23 | 4 | 6 | 50 | 22 | 32 | |
| 24 | 4 | 8 | 44 | 34 | 49 | |
| 25 | 4 | 10 | 40 | 46 | 67 | |
| 26 | 4 | 12 | 38 | 58 | 85 | |
| 27 | 4 | 15 | 35 | 76 | 111 | |
| 28 | 4 | 20 | 33 | 106 | 155 | |
| 29 | 4 | 26 | 31 | 142 | 208 | |
| 30 | 4 | 32 | 30 | 178 | 261 | |
| 31 | 4 | 38 | 29 | 214 | 313 | |
| 32 | 4 | 44 | 28 | 250 | 366 | |
| 33 | 4 | 4 | 50 | 14 | 20 | |

2-1-5 B3 (Special Barcode)

Description

Draw Special Barcode on the image buffer

Syntax

B3p1,p2,p3.....'DATA'

Parameters

p1 : Horizontal position (X) [dot]

p2 : Vertical position (Y) [dot]

p3 : Special barcode selection

| p3 | Special Barcode |
|-----------|-------------------------------|
| I | IMB(Intelligent Mail Barcode) |
| M | MSI Barcode |
| P | Plessey Barcode |
| T | TLC39 Barcode |
| R | RSS Barcode |

♣♣ Following parameters (p4, p5 ,Data) are barcodes-specific.

See the following pages for details of each special barcodes.

IMB (p3 = I)

p1 : Horizontal position (X) [dot]

p2 : Vertical position (Y) [dot]

p3 : I (means 'IMB')

p4 : Rotation

| Value | Rotation |
|--------------|-----------------|
| 0 | No Rotation |
| 1 | 90 degrees |
| 2 | 180 degrees |
| 3 | 270 degrees |

p5 : HRI

0 : Not Printed

1 : Below the barcode

'DATA' : ASCII data or Binary data.

Example

B3100,100,I,0,1,'0123456709498765432101234567891' // (p1,p2) is (100,100)

P1

MSI Barcode (p3 = M)

p1 : Horizontal position (X) [dot]

p2 : Vertical position (Y) [dot]

p3 : M (means 'MSI Barcode')

p4 : Narrow bar width [dot]

p5 : Wide bar width [dot]

p6: Barcode height [dot]

p7: Check digit selection

| Value | Rotation |
|-------|-----------------------|
| 0 | No check digits |
| 1 | 1 Mod 10 |
| 2 | 2 Mod 10 |
| 3 | 1 Mod 11 and 1 Mod 10 |

p8: Print check digit in HRI

0: Not print check digit

1: Print check digit

p9 : Rotation

| Value | Rotation |
|-------|-------------|
| 0 | No Rotation |
| 1 | 90 degrees |
| 2 | 180 degrees |
| 3 | 270 degrees |

p10 : HRI :

0 : Not printed

1 : Below the bar code

2 : Above the bar code

'DATA' : ASCII data or Binary data.

Example

```
B3100,100,M,2,7,150,1,1,0,1,'123456'
```

```
B3500,100,M,2,7,150,1,1,0,2,'123456'
```

```
B3100,100,M,2,7,150,1,1,0,1,'123456'
```

```
B3100,300,M,2,7,150,0,0,0,1,'123456'
```

```
P1
```

Plessey Barcode (p3 = P)

p1 : Horizontal position (X) [dot]

p2 : Vertical position (Y) [dot]

p3 : P (means 'Plessey Barcode')

p4 : Narrow bar width [dot]

p5 : Wide bar width [dot]

p6: Barcode height [dot]

p7: Print check digit

 0: Not print check digit

 1: Print check digit

p8 : Rotation

| Value | Rotation |
|-------|-------------|
| 0 | No Rotation |
| 1 | 90 degrees |
| 2 | 180 degrees |
| 3 | 270 degrees |

p9 : HRI :

 0 : Not printed

 1 : Below the bar code

 2 : Above the bar code

'DATA' : ASCII data or Binary data.

Example

```
B3450,100,P,2,7,150,1,0,2,'12345'
```

```
B350,100,P,2,7,150,1,0,1,'12345'
```

```
P1
```

TLC39 Barcode (p3 = T)

- p1** : Horizontal position (X) [dot]
- p2** : Vertical position (Y) [dot]
- p3** : T (means 'TLC39 Barcode')
- p4** : Narrow bar width of the Code39 [dot]
- p5** : Wide bar width of the Code 39[dot]
- p6** : Height of the cod39 [dot]
- p7** : Row height of the Micro PDF417: 1 ~ 255
- p8** : Narrow bar width of the Micro PDF417: 1~ 10
- p9** : Rotation

| Value | Rotation |
|--------------|-----------------|
| 0 | No Rotation |
| 1 | 90 degrees |
| 2 | 180 degrees |
| 3 | 270 degrees |

'DATA' : ASCII data or Binary data.

- Data structure : ECI Number,Serial Number,Additional data

| Data field | Description |
|-------------------|--|
| ECI Number | <p>ECI Number. If the seventh character is not a comma, only Code 39 prints. This means if more than 6 digits are present, Code 39 prints for the first six digits (and no Micro-PDF symbol is printed).</p> <ul style="list-style-type: none"> • Must be 6 digits. • Firmware generates invalid character error if the firmware sees anything but 6 digits. • This number is not padded. |
| Serial Number | <p>Serial number. The serial number can contain up to 25 characters and is variable length. The serial number is stored in the Micro-PDF symbol. If a comma follows the serial number, then additional data is used below.</p> <ul style="list-style-type: none"> • If present, must be alphanumeric (letters and numbers, no punctuation). • This value is used if a comma follows the ECI number. |
| Additional data | <p>Additional data. If present, it is used for things such as a country code.</p> <p>Data cannot exceed 150 bytes. This includes serial number commas.</p> <ul style="list-style-type: none"> • Additional data is stored in the Micro-PDF symbol and appended after the serial number. A comma must exist between each maximum of 25 characters in the additional fields. • Additional data fields can contain up to 25 alphanumeric characters per field. |

Example

B350,100,T,2,4,50,3,2,0,'123456,ABCD12345678901234,5551212,88899'

RSS Barcode (p3 = R)

p1 : Horizontal position (X) [dot]

p2 : Vertical position (Y) [dot]

p3 : R (means 'RSS Barcode')

p4 : RSS Barcode type

| Value | Barcode Type |
|-------|-------------------------------|
| 0 | RSS14 |
| 1 | RSS14 Truncated |
| 2 | RSS14 Stacked |
| 3 | RSS14 Stacked Omnidirectional |
| 4 | RSS Limited |
| 5 | RSS Expanded |
| 6 | UPC-A |
| 7 | UPC-E |
| 8 | EAN-13 |
| 9 | EAN-8 |
| 10 | UCC/EAN-128 and CC-A/B |
| 11 | UCC/EAN-128 and CC-C |

p5 : Magnification: 1 ~ 10

p6: Separator height: 1 ~ 2

p7: Barcode height [dot]

This parameter only affects the UCC/EAN barcode type and CC-A/B/C barcode type.

p8: The segment width: 0 ~ 22 (Even numbers only)

This parameter only affects the RSS Expanded barcode type.

p9 : Rotation

| Value | Rotation |
|-------|-------------|
| 0 | No Rotation |
| 1 | 90 degrees |
| 2 | 180 degrees |
| 3 | 270 degrees |

'DATA' : ASCII data or Binary data.

Example

B350,100,R,0,2,1,20,10,0,'12345678901|this is composite info'

P1

2-1-6 BD (Block Draw)

Description

Draw Line, Block, Box & Slope on the image buffer

Syntax

BDp1,p2,p3,p4,p5(,p6)

Parameters

p1 : Horizontal start position (X) [dot]

p2 : Vertical start position (Y) [dot]

p3 : Horizontal end position (X) [dot]

p4 : Vertical end position (Y) [dot]

p5 : Options

| p5 | Type | Additional p6 |
|-----------|-----------------------|---------------|
| O | Line Overwriting | Not necessary |
| E | Line Exclusive OR | Not necessary |
| D | Line Delete | Not necessary |
| S | Slope(a oblique line) | Thickness |
| B | Box | Thickness |


♣ If p5 is S or B, then additional p6 must follow p5.

Example


1) Start and end position




2) Overwriting mode(when p5 is O)




3) Exclusive OR mode(when p5 is E)




4) Delete block mode(when p5 is D)



5) Slope block mode(when p5 is S)



6) Draw box mode(when p5 is B)



2-1-7 CD (Circle Draw)

Description

Draw Circle on the image buffer

Syntax

CDp1,p2,p3,p4

Parameters

p1 : Horizontal start position (X) [dot]

p2 : Vertical start position (Y) [dot]


p3 : Circle Size Selection

| Value | Diameter (mm) | Width × Height(dots) |
|-------|---------------|----------------------|
| 1 | 5 | 40 × 40 |
| 2 | 7 | 56 × 56 |
| 3 | 9 | 72 × 72 |
| 4 | 11 | 88 × 88 |
| 5 | 13 | 104 × 104 |
| 6 | 21 | 168 × 168 |

p4 : Multiplier : 1 ~ 4

Example

CD100,200,2,1



2-1-8 CS (Character Set selection)

Description

To select International Character Set(ICS) and Code Page Table.

Syntax

CS*p1,p2*

Parameters

p1 : International Character Set

| p1 | Country |
|-----------|------------------|
| 0 | U.S.A |
| 1 | France |
| 2 | Germany |
| 3 | U.K |
| 4 | Denmark I |
| 5 | Sweden |
| 6 | Italy |
| 7 | Spain I |
| 8 | Norway |
| 9 | Denmark II |
| 10 | Japan |
| 11 | Spain II |
| 12 | Latin America |
| 13 | Korea |
| 14 | Slovenia/Croatia |
| 15 | China |

p2 : Code Pages

| p2 | Code Table | Language |
|-----------|-------------------|-------------------|
| 0 | CP437 | U.S.A |
| 1 | CP850 | Latin 1 |
| 2 | CP 852 | Latin 2 |
| 3 | CP 860 | Portuguese |
| 4 | CP 863 | Canadian French |
| 5 | CP 865 | Nordic |
| 6 | WCP 1252 | Latin I |
| 7 | CP 865 + WCP 1252 | European Combined |
| 8 | CP 857 | Turkish |
| 9 | CP 737 | Greek |
| 10 | WCP 1250 | Latin 2 |
| 11 | WCP 1253 | Greek |
| 12 | WCP 1254 | Turkish |
| 13 | CP 855 | Cyrillic |
| 14 | CP 862 | Hebrew |
| 15 | CP 866 | Cyrillic |
| 16 | WCP 1251 | Cyrillic |
| 17 | WCP 1255 | Hebrew |
| 18 | CP 928 | Greek |
| 19 | CP 864 | Arabic |
| 20 | CP 775 | Baltic |
| 21 | WCP1257 | Baltic |
| 22 | CP858 | Latin 1 + Euro |

♣ Default Setting is U.S.A standard (p1=0 and p2=0).

♣ European Combined Page

| Address | Code Page |
|----------------|------------------|
| 0x80 | Euro Currency |
| 0x81 ~ 0x9f | PC865 |
| 0xA0 ~ 0xff | PC1252 |

| Country | International Character Set | | | | | | | | | | | | | |
|------------------|-----------------------------|-----|-----|-----|-----|---------|---------|-----|-----|-----|---------|---------|-----|--|
| | Hex | 23h | 24h | 40h | 5Bh | 5C h | 5D h | 5Eh | 60h | 7Bh | 7C h | 7D h | 7E | |
| | Dec | 35 | 36 | 64 | 91 | 92 | 93 | 94 | 96 | 123 | 123 | 125 | 126 | |
| U.S.A | # | \$ | @ | [| \ |] | ^ | ` | { | | } | ~ | | |
| France | # | \$ | à | ° | ç | § | ^ | ` | é | ù | è | “ | | |
| Germany | # | \$ | § | Ä | Ö | Ü | ^ | ` | ä | ö | ü | ß | | |
| U.K. | £ | \$ | @ | [| \ |] | ^ | ` | { | | } | ~ | | |
| Denmark I | # | \$ | @ | Æ | Ø | Å | ^ | ` | æ | ø | å | ~ | | |
| Sweden | # | ¤ | É | Ä | Ö | Å | Ü | é | ä | ö | å | ü | | |
| Italy | # | \$ | @ | ° | \ | é | ^ | ù | à | ò | è | ì | | |
| Spain | Pts | \$ | @ | i | Ñ | ¿ | ^ | ` | .. | ñ | } | ~ | | |
| Norway | # | ¤ | É | Æ | Ø | Å | Ü | é | æ | ø | å | ü | | |
| Denmark II | # | \$ | É | Æ | Ø | Å | Ü | é | æ | ø | å | ü | | |
| Japan | # | \$ | @ | [| ¥ |] | ^ | ` | { | | } | ~ | | |
| Spain II | # | \$ | á | i | Ñ | ¿ | é | ` | í | ñ | ó | ú | | |
| Latin America | # | \$ | á | i | Ñ | ¿ | é | ü | í | ñ | ó | ú | | |
| Korea | # | \$ | @ | [| \ |] | ^ | ` | { | | } | ~ | | |
| Slovenia/Croatia | # | \$ | ž | š | Đ | Ć | Č | ž | š | đ | ć | č | | |
| China | # | ¥ | @ | [| \ |] | ^ | ` | { | | } | ~ | | |

| ASCII Code | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | A | B | C | D | E | F |
|---------------|-----|---|---|---|----|---|---|---|---|---|---|---|---|---|---|----|
| | 0 | | | | | | | | | | | | | | | |
| | 0 | | | | | | | | | | | | | | | |
| | 1 | | | | | | | | | | | | | | | |
| | 16 | | | | | | | | | | | | | | | |
| | 2 | ! | " | # | \$ | % | & | ' | (|) | * | + | , | - | . | / |
| | 32 | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | : | ; | < | = | > |
| | 48 | @ | A | B | C | D | E | F | G | H | I | J | K | L | M | O |
| | 64 | P | Q | R | S | T | U | V | W | X | Y | Z | [|] | ^ | -` |
| | 80 | a | b | c | d | e | f | g | h | i | j | k | l | m | n | o |
| | 96 | q | r | s | t | u | v | w | x | y | z | { | | } | ~ | □ |
| | 112 | | | | | | | | | | | | | | | |

* Refer to the “Code Pages Manual” for more extension code pages table.

2-1-9 P (Print)

Description

Let the printer start printing the content of image buffer

Syntax

P[]

Parameters

p1 : Number of label sets : 1 ~ 65535

p2 : Number of copies of each label : 1 ~ 65535

♣ The P command cannot be used in a template sequence. If printing command is needed in template sequence, then use the PV command(See the example of next page).



Caution

The 'P' command should be terminated by 'CR'(0x0d). If not, the printer will not start to print until 'CR' comes.

Example

(1) In case of Using P (P is used outside of template sequence)

```
TS'TPL_TST1'                                // Start Template Store
SV00,15,N,'Model Name :'                    // Declare variable V00
T50,100,3,1,1,0,0,N,N,'Model Name :V00    // T command with variable
TE                                         // End Template Store

TR'TPL_TST1"                                // Recall stored template 'TPL_TST1'
?                                           // Get content of variable used in recalled template
XT5-40                                     // Content of variable V00
P3,2                                         // when using P command, It must not be inside
                                             // template
                                             // but be used after recalling the template and entering
                                             // the contents of all variables.

// After P command, printer starts printing.
```

(2) In case of Using PV(PV is used inside of template sequence)

```
TS'TPL_TST1'                                // Start Template Store
SV00,15,N,'Model Name :'                    // Declare variable V00
SV01,2,N,'# of set :'                     // Declare variable V01
SV02,2,N,'# of copies : '                 // Declare variable V02
T50,100,3,1,1,0,0,N,N,'Model Name :V00    // T command with variable
PVV01,V02                                   // PV command can be used inside the template
TE                                         // End Template Store

TR'TPL_TST1"                                // Recall stored template 'TPL_TST1'
?                                           // Get content of variable used in recalled template
XT5-40                                     // Content of variable V00
3                                           // Content of variable V01
2                                           // Content of variable V02

// As soon as all contents of variables are entered
// printer will starts printing
```

2-2 Media Buffer Related Commands

1) ST

Select thermal direct/transfer printing mode.

2) SM

Set marginal value in label(Image buffer).

3) SF

Set back-feed option.

4) SL

Set label(Image buffer) length.

5) SW

Set label(Image buffer) width.

6) CB

Clear image buffer.

7) CL

Set calibration checking length.

2-2-1 ST (Set Printing Type)

Description

Select thermal direct printing or thermal transfer printing.

Syntax

ST*p1*

Parameters

p1 : Direct thermal / thermal transfer

- d : Direct thermal
- t : Thermal transfer

2-2-2 SM (Set Margin)

Description

Set marginal value of the image buffer.

This command moves the origin point (0,0) to (p1,p2)
and make (p1,p2) become the new origin.

Syntax

SM*p1,p2*


Parameters

p1 : Horizontal margin [dots]


p2 : Vertical margin [dots]

♣ The origin point is upper-left point of the image buffer

** When printing orientation is from top to bottom



** When printing orientation is from bottom to top.



2-2-3 SF (Set Back-Feed Option)

Description

Set back-feed option.

This command decides whether printer does back-feed action before starting printing.

Syntax

SFp1(,p2)

Parameters

p1 : Enable/Disable

- 0 : Disable back-feed option.
- 1 : Enable back-feed option(Default)

p2 : Back feeding step quantity.

- This parameter is valid when p1 is 1.
- The step quantity defined by user can't exceed printer's default feeding quantity.
- 0 means printer's default feeding quantity.

-
- ♣ This option is useful for the continuous paper or black mark media with perforation line away from black mark.
 - ♣ The printer's default back feeding step quantity depends on the printer models and printer modes such as normal, peeler or cutter.
-

Examples

| | |
|---------|---|
| SF0 | → Disable Printer's back-feeding option |
| SF1 | → Default quantity of Back feed is executed before printing |
| SL1,0 | → Default quantity of Back feed is executed before printing |
| SL1,100 | → 100 step's Back feed is executed before printing |
| SL0,100 | → Back feed is disabled and p2(100) is ignored |

2-2-4 SL (Set Length)

Description

Set length of label and gap(or Black Mark) and specify media type.

Syntax

SLp1,p2(,p3)(,p4)

Parameters

p1 : Label length [dots] : Maximum 2432 dots(12 inch)

- ♣ Double buffering feature can be used only when label length(p1) is less than 1216(2432/2, 6inch) dots.
- ♣ If p1 is over 1216 dots, the double buffering feature will be automatically released.
- ♣ So if you don't use double buffering feature, you can design maximum 2432 dots(12 inch) size label.

p2 : Gap length or thickness of black line [dots]

p3 : Media Type

| p3 | Media type |
|-----------|-------------------|
| G | Gap |
| C | Continuous |
| B | Black Mark |

- ♣ If this parameter is not used, automatically set to G(Gap type).
- ♣ The default value of label length is 6 inch(1216 dots)
- ♣ This command sets the length of image buffer and the printer will print and form feed as much as the length set by this command.
- ♣ When using Continuous type media, the label length must be set.

p4 : Offset Length between Black Mark(or Gap) and perforation line [dots]

- ♣ This parameter is valid when p3 parameter is used.

Examples

| | |
|-------------|---|
| SL1200,20 | → Gap media, Media length:1200dots,Gap length:20dots |
| SL1200,20,C | → Continuous media, Media length:1200dots,Gap length:20dots |
| SL1200,20,G | → Gap media, Media length:1200dots,Gap length:20dots |
| SL1200,20,B | → Black mark media, Media length:1200dots,Gap length:20dots |

The perforation line is on the black mark.

SL1200,20,B,200 → Black Mark media, Media length:1200dots,Gap length:20dots

The perforation line is 200 dots behind from black mark.


♣ In the Gap Mode, the printer will form feed until meeting the next gap.

♣ In the Continuous Mode, the printer will form feed as much as label length set by SL.

♣ In the B/M Mode, the printer will form feed until meeting the next B/M.


Example – p1 & p2(Length)

SL406,20 // Set label length to 406 dots (2 inch, 50mm) and gap length to 20 dots(2.5mm)



Example – p3(Media Type)


1. Gap Type




2. Continuous Type



3. Black Mark Type



Example – p4(Offset Length)



2-2-5 SW (Set Width)

Description

Set label width.

Resize the image buffer to match the label size.

Syntax

SWp1


Parameters

p1 : Label width [dots]

- ◆ The default value of label width is 4.1 inch(832 dots) and that is the maximum printable width.
- ◆ Every Printer except XT5-40 is the center aligned and media is positioned in the center of the head.
- ◆ XT5-40 is the left aligned and media is positioned in the left of the head.
(Standard for industrial label printer)

Example

```
SW406 // Set label width to 2 inch(406 dots)
```



2-2-6 CB (Clear Buffer)

Description

Clear image buffer and be ready to make a new label.

Syntax

CB

Example

| | |
|----|-----------------------|
| CB | // Clear Image Buffer |
|----|-----------------------|

2-2-7 CL (Calibration Length setting)

Description

Set calibration checking length in mm units.

Syntax

CL*p1*

Parameters

p1 : Calibration checking length [mm]

♣ Calibration checking length Minimum 150mm, Default 600mm, Maximum 2000mm

예제

| | |
|--------|--|
| CL1200 | // Set Calibration Checking Length in 1200mm |
|--------|--|

♣ Calibration checking length would be saved in printer memory by using CL command.

2-3 Printer Setting Commands

1) SS

Set printer speed

2) SD

Set printing density

3) SO

Set printing orientation

4) SP

Set serial port

5) SA

Set Offset

6) TA

Set Tear-off/Cut

2-3-1 SS (Set Speed)

Description

Set print speed

Syntax

SSp1

Parameters

p1 : Speed set value

| Value | Speed |
|-------|---------|
| 0 | 2.5 ips |
| 1 | 3.0 ips |
| 2 | 4.0 ips |
| 3 | 5.0 ips |
| 4 | 6.0 ips |
| 5 | 7.0 ips |
| 6 | 8.0 ips |

2-3-2 SD (Set Density)

Description

Set printing density

Syntax

SDp1

Parameters

p1 : Density Level

- 0 ~ 20 (0 is the lowest density)

2-3-3 SO (Set Orientation)

Description

Set printing direction

Syntax

SOp1

Parameters

p1 : Printing direction


T : Print from top to bottom(default)

B : Print from bottom to top

Example

```
SOT          // Print from top of the image buffer to bottom.  
SOB          // Print from bottom of the image buffer to top.
```

Printing Direction



2-3-4 SP (Set Port)

Description

Set serial port.

Syntax

SP*p1,p2,p3,p4*

Parameters

p1 : Baud rate

| Value | Baud Rate(bps) |
|-------|----------------|
| 0 | 9,600 |
| 1 | 19,200 |
| 2 | 38,400 |
| 3 | 57,600 |
| 4 | 115,200 |

p2 : Parity

| Value | Parity |
|-------|---------------------------|
| O | Odd parity |
| E | Even parity |
| N | No parity(Default) |

p3 : Number of data bits

| Value | Data bits |
|-------|-------------------------|
| 7 | 7 bit |
| 8 | 8 bits (Default) |

p4 : Number of stop bits

| Value | Stop bits |
|-------|-----------------------|
| 1 | 1 bit(Default) |
| 2 | 2 bits |

2-3-5 SA (Set Offset)

Description

Save (set) offset length between black marks (or gap) and dotted lines [dots]

Syntax

SA*p1*

Parameters

p1 : -100~100

-
- ◆ Offset values saved via the use of SA commands are stored permanently on the printer.
(Offset values saved via the cf. SL command are reset after the power is turned off.)
-

2-3-6 TA (Tear-off/Cutter Position Setting)

Description

This function regulates the label cutting location after printing.

Tear-off position or Cut position can adjust.

Syntax

TA*p1*

Parameters

p1 : -100~100

-
- ◆ Tear-off/Cutter Position values saved via the use of TA commands are stored permanently on the printer.
-

2-4 Variable Related Commands

1) SC

Counters which is used in template sequence

2) AC(Auto Counter)

Counters which is used in normal commands sequence
(outside of template sequence)

3) SV

Set variable

4) ?

Get data for counter and variable

5) PV

Print with variables

2-4-1 SC (Set Counter)

Description

Define one counter of total 10 counters.

Counters must be used in Template sequence and execute consecutive auto-numbering function.

Syntax

SCp1,p2,p3,p4,'Prompt'

Parameters

p1: Identity of Counter : 0 ~ 9

♣ Total 10 counters, from C0 to C9, are provided.

p2: The size of the field which displays the content of counter : 1 ~ 27

p3: Justification in field(Field size is p2)

| Value | Justification |
|-------|---------------|
| N | No |
| R | Right |
| L | Left |
| C | Center |

p4 : Step Value : ±1 ~ ±9

♣ + or - symbol must precede . Ex) -2 or +3

'Prompt': This text string is transmitted to host(PC) by serial interface in order to give information to host about the declared counter.

♣ The data field of T(Text) or B(Barcode) commands is used to print the contents of counter.

♣ SC should be used just in Template sequence. If you want to use counter function in normal mode(not in Template), use the AC(Auto Counter).

Example

SC0,7,N,+3,'Please Enter Serial Number'

2-4-2 AC (Auto Counter)

Description

Define one counter of total 10 counters.

Counters can be used in normal mode(not in Template) and execute consecutive auto-numbering.

Syntax

ACp1,p2,p3,'Start Value'

Parameters

p1 : Identity of Counter : 0 ~ 9

♣ Total 10 counters, from C0 to C9, are provided.

p2 : The size of the field which displays the content of counter : 1 ~ 27

p3 : Step Value : ±1 ~ ±9

♣ + or – symbol must precede . Ex) –2 or +3

'Start Value' : Start value of auto-counting. Just digits can be used in this field

-
- ♣ The Auto-counter defined by AC command can be printed with T and B1 command.
 - ♣ This function is useful to print serial number or serial barcode without using Template.
 - ♣ AC cannot be used in Template sequence. If you want to use counter function in Template sequence, use the SC command.
-

Example

```
AC0,3,+1,'123'          // Please input the start value of counting between ' mark
AC1,7,+1,'1234567'
```

```
T100,100,3,1,1,0,0,N,N,C0
B1100,400,0,2,7,100,0,1,12,C1
```

```
P3,1
```

2-4-3 SV (Set Variable)

Description

Define variables for the text or barcode ‘data’ fields.

Syntax

SVp1,p2,p3,’Prompt’

Parameters

p1 : Identity of Variables : 00 ~ 99

p2 : Maximum number of characters : 1 ~ 99

p3 : Justification in field(Field size is p2)

| Value | Justification |
|-------|---------------|
| N | No |
| R | Right |
| L | Left |
| C | Center |

‘Prompt’: This ASCII text field is used to ask a value to be entered for the variable(p1) and is transmitted to the host by serial interface.

-
- ♣ The data field of T(Text) or B(Barcode) commands is used to print the contents of variable.
 - ♣ Variable is entered to data field like V00 or V01.
 - ♣ If variable characters have smaller number than parameter2(p2), remain characters are padded by null data(0x20) in barcode printing .
-

Example

SV01,20,N,’Please Enter Product Code :’

2-4-4 ? (Get Variables)

Description

Use this command to get the content of variables or counters

Syntax

?

Content of variable

♣ Data must be entered in ascending order

Example

```
TS'Template1'          // Template Store Start
SV00,20,N,'Enter Company Name : ' // Declare(Set) variable V00
SV01,15,N,'Enter Product Code : ' // Declare(Set) variable V01
T50,30,3,1,1,0,0,N,N,V00        // Use T command to print V00
T50,150,3,1,1,0,0,N,N,'Code : 'V01 // Use T command to print V01

TE                      // Template Store End

TR'Template1'          // Recall Template1
?                      // Start to get data for variables
BIXOLON                // data for V00
XT5-40                  // data for V01
P1                      // Start Printing when the P command comes
```

Result

```
BIXOLON
Code : XT5-40
```

2-4-5 PV (Print with Variables)

Description

This command is used in template sequence.

The parameters are given by variables.

Syntax

PVp1,[p2]

Parameters

p1 : Number of label sets : 1 ~ 65535

p2 : Number of copies of each label : 1 ~ 65535

Example

```
TS'Template1'  
SV00,20,N,'Please Input the Name :'  
SV01,5,N,'Input Number of label sets :'  
SV02,5,N,'Input Number of label copies :'  
T50,30,3,1,1,0,0,N,N,V00  
PVV01,V02  
TE  
  
TR'Template1'  
?  
This is PV Test  
2  
1
```

// Template Store Start
// Declare(Set) variable V00
// Declare(Set) variable V01
// Declare(Set) variable V02
// Write V00 to image buffer
// Print V00, V02 copies, V01 sets
// Template Store End

// Recall Template1
// Start to get data for variables
// data for V00
// data for V01
// data for V02

***** Start Printing as soon as data for all variables(and counters) are entered. *****

2-5 Template Related Commands

Template(a certain format of label, sequence of SLCS commands) related commands

1) TS

Indicate start of template sequence store.

2) TE

Indicate end of template sequence store.

3) TR

Recall and reuse stored template.

4) TD

Delete stored template.

5) TI

Print the list of all templates stored in memory.

6) TN

Transfer the list of all templates stored in memory to the HOST.

7) TT

Transfer the contents of the specific template stored in memory to the HOST.

2-5-1 TS (Template store Start)

Description

Start template sequence storing.

All the contents following 'TS' are stored in memory until meeting 'TE' Command.

Syntax

TS '*Template name*'

Parameters

'**Template name**': This name will be used when 'Recall' the stored template.

- ♣ The name is allowed to be up to 10 characters long.
- ♣ The 'Template name' is **Case-Sensitive**.

♣ **TI command shows the list of currently stored Templates.**

2-5-2 TE (Template store End)

Description

End template sequence storing

Syntax

TE

♣ **When storing is finished, the printer sends '!' to the host to prompt end of storing.**

Example

```
TS'Template1'          // Start template storing
.....
TE                  // End template storing
```

2-5-3 TR (Template Recall)

Description

Recall the stored template from memory to make a label and print that.

Syntax

TR '*Template name*'

Parameters

'**Template name**' : Indicate the template to be recalled.

- ♣ The name is allowed to be up to 10 characters long.
- ♣ The 'Template name' is **Case-Sensitive**.

Example

```
TR'Template1'           // Recall 'Template1'
```

-
- ♣ If recalled Template does not include any variable or counter, just 'P' command is enough to start printing.
 - ♣ If recalled Template includes variables or counters but not 'PV'(Print with Variables), use '?' command to get data for variables and counters and finally 'P' command is necessary to start printing.
 - ♣ If recalled Template includes PV commands, printing will start as soon as all data for variables and counters are entered.
-

2-5-4 TD (Template Delete)

Description

Delete stored template from memory

Syntax

TD '*Template name*'

Parameters

'**Template name**' : Indicate the template to be deleted.

- ♣ The name is allowed to be up to 10 characters long.
- ♣ The 'Template name' is **Case Sensitive**.
- ♣ By using *, all templates will be deleted from memory.

Example

```
TD'Template1'          // Delete 'Template1'  
TD*                   // Delete all currently stored templates
```

2-5-5 TI (Template Information)

Description

Print list of currently stored templates and available memory space

Syntax

TI

Example

```
TI
```

Result

```
Templates Information  
=====  
1. Template1  
2. Template2  
Available template memory : 53Kbyte
```

2-5-6 TN (Template Name)

Description

Transfer memory saved template lists to HOST

Syntax

TN

-
- ♣ Each template name separates with Comma(,)
 - ♣ If there is no saved template, it will return NULL value.
-

Example

| | | |
|---|---------------------------------------|---------|
| TN | // Request memory saved template list | SEND |
| → Tmplname1, Tmplname2,....., TmplnameN | // Receive saved template lists | RECEIVE |

2-5-7 TT (Template Transfer)

Description

Transfer memory saved template contents to HOST

Syntax

TT 'Template name'

Parameters

'Template name' : Select template name you want to receive.

- ♣ Name length can be 10 characters.
- ♣ Template name recognizes a capital case.

-
- ♣ Printer would notify template end by transferring Null value after the end of the template contents.
-

Example

| | | |
|---|--|---------|
| TT'Template1' | // Request memory saved template1's contents | SEND |
| → SV00,20,N,'Please Input the Name :' | | RECEIVE |
| SV01,5,N,'Input Number of label sets :' | | |
| SV02,5,N,'Input Number of label copies :' | | |
| T50,30,3,1,1,0,0,N,N,V00 | | |
| PVV01,V02 | // Receive all template1's contents | |

2-6 Image Related Commands

These commands provide functions to download and print graphic data.

PCX and BMP format file are supported and bitmap image data can be printed directly.

1) IS

Download PCX format image data to NV(Non Volatile) area of memory.

2) IR

Recall and print downloaded image data.

3) ID

Delete image data in NV memory.

4) II

Print all images stored in memory.

5) LD

Draw the bitmap image data directly on specific position on image buffer.

6) LC

Draw compression bitmap image data on specific position of image buffer.

7) BMP

Draw BMP format image file directly on specific position on image buffer.

2-6-1 IS (Image Store)

Description

Download PCX format Image file into the Printer Memory

Syntax

IS*p1, 'Image name'DATA OF *.PCX*

Parameters

p1 : The size of image file in unit of byte.

'Image name' : This is the name that will be used when recalling the stored image data.

♣ The name is allowed to be up to 10 characters long.

♣ The name is case sensitive.

DATA OF *.PCX : Binary data string of PCX file.

2-6-2 IR (Image Recall)

Description

Recall the stored image from memory and draw that on the image buffer.

Syntax

IR*p1,p2, 'Image name'*

Parameters

p1 : Horizontal position (X) [dot]

p2 : Vertical position (Y) [dot]

'Image name' : Indicate the image data to be recalled.

♣ Variable can be used in this field.

♣ The name is allowed to be up to 10 characters long.

♣ This name is Case Sensitive.

Example

```
IR30,100,'Image1'          // Recall 'Image1'  
IR30,100,V01               // Variable can be used in name field
```

2-6-3 ID (Image Delete)

Description

Delete stored image from memory

Syntax

ID'Image name'

Parameters

'Image name' : Indicate the Image in memory to be deleted.

- ♣ The name is allowed to be up to 10 characters long.
- ♣ This name is **Case Sensitive**.
- ♣ By using *, all images in memory will be deleted.

Example

```
ID'Image1'          // Delete 'Image1'  
ID*                // Delete all currently stored images
```

2-6-4 II (Image Information)

Description

Print list of currently stored images in memory and available memory space.

Syntax

II

Example

```
II
```

Result

```
Image Information  
=====  
1. Image1  
2. Image2  
Available Images memory : 5.3Kbyte
```

2-6-5 LD

Draw bitmap image data on specific position of image buffer.

Syntax

LDxL xH yL yH dhL dhH dvL dvH d1~dk

Parameters

xL : **Low byte** of horizontal **start position (X)** [dot]

xH : **High byte** of horizontal **start position (X)** [dot]

→ Start position in x direction = $xH * 256 + xL$

yL : **Low byte** of vertical**start position (Y)** [dot]

yH : **High byte** of vertical **start position (Y)** [dot]

→ Start position in y direction = $yH * 256 + yL$

dhL : **Low byte** of the **number of bytes in x-direction**.

dhH : **High byte** of the **number of bytes in x-direction**.

→ Number of data in x direction = $dhH * 256 + dhL$

dvL : **Low byte** of the **number of lines**.

dvH : **High byte** of the **number of lines**.

→ Number of data in y direction = $dvH * 256 + dvL$

d1~dk : **bitmap image data**.

→ $k = (dhH*256 + dhL) * (dvH*256 + dvL)$



Caution


There are no comma (,) and no space between each parameters.

Example

LD 0x11 0x02 0x40 0x02 0x08 0x00 0x20 0x00 0xFF ~ 0xFF

① ② ③ ④ ⑤

- ① x position : $0x02 * 0x100(256) + 0x11 = 0x211(529)$
- ② y position : $0x02 * 0x100(256) + 0x40 = 0x240(576)$
- ③ horizontal data number : $0x00 * 0x100(256) + 0x08 = 0x08(8)$
- ④ vertical data number : $0x00 * 0x100(256) + 0x20 = 0x20(32)$
- ⑤ bitmap data : total number = $8 * 32 = 256$



2-6-6 LC

Draw compression bitmap image data on specific position of image buffer

Syntax

LCp1p2xL xH yL yH dhL dhH dvL dvH d1~dk

Parameters

p1: Compression type

R: RLE

p2: Color

0x00: black

0x01: Color(red or blue)

xL : Low byte of horizontal start position (X) [dot]

xH : High byte of horizontal start position (X) [dot]

→ Start position in x direction = $xH * 256 + xL$

yL : Low byte of vertical start position (Y) [dot]

yH : High byte of vertical start position (Y) [dot]

→ Start position in y direction = $yH * 256 + yL$

dhL : Low byte of the number of bytes in x-direction.

dhH : High byte of the number of bytes in x-direction.

→ Number of data in x direction = $dhH * 256 + dhL$

dvL : Low byte of the number of lines.

dvH : High byte of the number of lines.

→ Number of data in y direction = $dvH * 256 + dvL$

d1~dk : Compression bitmap image data.

→ k = $(dhH*256 + dhL) * (dvH*256 + dvL)$



Caution


There are no comma (,) and no space between each parameters.

Example

LC R 0x00 0x11 0x02 0x40 0x02 0x08 0x00 0x20 0x00 0xFF ~ 0xFF

① ② ③ ④ ⑤ ⑥ ⑦

- ①Compression type : R =RLE
- ②Color : 0x00 = Black
- ③x position : $0x02 * 0x100(256) + 0x11 = 0x211(529)$
- ④y position : $0x02 * 0x100(256) + 0x40 = 0x240(576)$
- ⑤horizontal data number : $0x00 * 0x100(256) + 0x08 = 0x08(8)$
- ⑥vertical data number : $0x00 * 0x100(256) + 0x20 = 0x20(32)$
- ⑦bitmap data : total number = $8 * 32 = 256$



※ RLE compression

This is the algorithm to compress the continuous data.

The compression is applied to 0x00 & 0xff data but not the others.

0xff 0x04 data is created if 0xff is repeated four times like 0x00 0x00 0x00 0x00.

In the same way, 0x00 0x04 is created by four times repeats of 0x00 such as 0x00 0x00 0x00 0x00.

Here is the example of compression.

Example) 0x78 0x78 0xff 0xff 0xff 0xff 0x22 0x00 0x00 0x00 0x00

0x78 0x78 0xff 0x05 0x22 0x00 0x04

2-6-7 BMP

Send BMP format file directly to printer.
Just white/black BMP file is supported

Syntax

BMPp1,p2↓
Data String of *.bmp

Parameters

p1 : Horizontal position (X) [dot]
p2 : Vertical position (Y) [dot]

-
1. ↓ means 'CR(+LF)'
 2. There is comma(,) between p1 and p2.
 3. After p2(Before sending BMP data string) 'CR(+LF)' must follow.
-

Example

In DOS mode,
COPY bmp.txt+image2.bmp+P.txt LPT1 /b

Bmp.txt

BMP200,200 ↓

P.txt

P1 ↓

2-7 Downloadable font Related Commands

Download fonts into the printer memory. Users can download special size or special design of ASCII font and use this font with T command.

1) DT

Download True Type Font into Printer Memory

2) DD

Delete downloaded fonts from memory

3) DI

Print all downloaded fonts in memory and available memory space.

2-7-1 DT (Download True Type Font)

Description

Download windows system font into printer memory.

Syntax

DTp1,p2,'Font Name' a₁b₁(DATA₁)a₂b₂(DATA₂)...a_nb_n(DATA_n)

Parameters

p1 : Total number of characters to be downloaded: 0~255

p2 : Font Height: 0~255

Font name : A ~ Z

a_n : Character position in ASCII Table(0~255)


b_n : Font width(dots)

(DATA_n) : Character Bitmap Data

Total bytes of bitmap data : **p2 × (b_n+7)/8** bytes

Example

| | |
|--|--------------|
| 44 44 2a 0d 0a 44 54 60 14 27 41 27 | DD*..DT..'A' |
| 20 0b | |
| ↑ ↑ ↑ | |
| a ₁ b ₁ DATA ₁ : p2×(b ₁ +7)/8 bytes | |
| 21 0c | |
| ↑ ↑ ↑ | |
| a ₂ b ₂ DATA ₂ : p2×(b ₂ +7)/8 bytes | |



2-7-2 DD (Downloaded font Delete)

Description

Delete downloaded font from memory

Syntax

DD '*font name*'

Parameters

'*font name*' : Indicate the Image in memory to be deleted.(A~Z)

- ♣ This name is Case Sensitive.
- ♣ By using *, all images in memory will be deleted.
- ♣ You can show the downloaded font list by DI command.

Example

| | |
|-------|--|
| DD'A' | // Delete downloaded font A |
| DD* | // Delete all downloaded fonts in memory |

2-7-3 DI (Downloaded font Information)

Description

Print list of downloaded font.

Syntax

DI

Example

DI

Result

```
Download Font Information
=====
Name      w   h   c   Size
=====
C         16  25  128  6400
G         12  24  224  10752

Free Memory          179419
=====
```

♣ **w** : font width, **h** : font height, **c**: total number of characters

2-8 The Others

Commands not included in 1 to 7 categories.

1) @

Printer initialization

2) PI

Print information of printer configuration

3) CUT

Enable/Disable Cutting Action

4) ^cp

Check printer status and report 2bytes status data to host.

5) ^cu

Check printer status and report 1byte status data to host.

6) ^PI

Send various printer information to host.

2-8-1 @ (Initialize Printer)

Description

Initialize the printer

Syntax

@

2-8-2 PI (Printer Information)

Description

Print current printer setting.

Syntax

PI

2-8-3 CUT (Auto-cutter Enable/Disable)

Description

Cutter Enable/Disable

Syntax

CUTp1(,p2)

Parameters

p1: Cutting Action Enable/Disable

y : Enable cutter to act after printing is finished.

n : Disable cutter.

p2 : Cutting Period

◆ Cutting Period means the number of pages between two cuttings.

◆ Last page is always cut.

Example – p1(Cutter Enable/Disable)

| Cutting is executed after Printing is finished | Cutting is not executed after Printing is finished |
|--|--|
| T20... B130... BD... ... CUTy P1 | T20... B130... BD... ... CUTn P1 |

Example – p2(Cutting Period)

```
CUTy           // Cut every page  
CUTy,1        // Cut every page  
CUTy,2        // Cut every 2 pages  
CUTy,4        // Cut every 4 pages
```

2-8-4 ^cp (Check Printer Status and Report 2 bytes)

Description

Check printer status and report 2bytes status data to host.

Syntax

^cp

Return Value

1. Format

<1st Byte> <2nd Byte>

2. Table

| Return Values | | Description | Hex |
|---------------|-----|--|------|
| Byte | bit | | |
| 1st Byte | 7 | Paper Empty | 0x80 |
| | 6 | Cover Open | 0x40 |
| | 5 | Cutter jammed | 0x20 |
| | 4 | Thermal Head(TPH) overheat. | 0x10 |
| | 3 | Gap Detection Error(Auto-sensing failure) | 0x08 |
| | 2 | Ribbon End Error | 0x04 |
| | 1 | Not assigned | 0x02 |
| | 0 | Not assigned | 0x01 |
| 2nd Byte | 7 | On building label to be printed in image buffer. | 0x80 |
| | 6 | On printing label in image buffer | 0x40 |
| | 5 | Issued label is paused in peeler unit. | 0x20 |
| | 4 | Not assigned | 0x10 |
| | 3 | Not assigned | 0x08 |
| | 2 | Not assigned | 0x04 |
| | 1 | Not assigned | 0x02 |
| | 0 | Not assigned | 0x01 |

3. Examples

| When Return Values are | | Printer Status is |
|------------------------|----------|---|
| 1st Byte | 2nd Byte | |
| 0x00 | 0x00 | No Error. The printer is ready to build and print label. |
| 0x80 | 0x00 | No paper is installed in printer. |
| 0x80 | 0x40 | Paper roll out while printing label. When new paper roll is loaded, the printer will re-issue the last label. |
| 0x60 | 0x40 | While printing, cutter is jammed and cover is opened (by user). |

2-8-5 ^cu (Check Printer Status and Report 1 byte)

Description

Check printer status and report 1 byte status data to host.

Syntax

^cu

Return Value

1. Format

<1st Byte>

2. Table

| Return Values | | Description | Hex |
|---------------|-----|---|------|
| Byte | bit | | |
| 1st Byte | 7 | Paper Empty | 0x80 |
| | 6 | Cover Open | 0x40 |
| | 5 | Cutter jammed | 0x20 |
| | 4 | Thermal Head(TPH) overheat. | 0x10 |
| | 3 | Gap Detection Error(Auto-sensing failure) | 0x08 |
| | 2 | Ribbon End | 0x04 |
| | 1 | Not assigned | 0x02 |
| | 0 | Not assigned | 0x01 |

2-8-6 ^PI (Send Printer information to host)

Description

Send various printer information such as model name, firmware version, statistics data or so to host.

Syntax

^PI(p1,(p2),(p3))

Parameters

p1 : items to be reported.

0 : Model Name

2 : F/W Version

3 : Mechanical Conditions of Printer

4 : Usb Serial Number Information

5 : Bluetooth Mfi Serial Number Information

→ **(p2), (p3)** : Used only when (p1=3)

Present -> From power on / **Permanent** -> From the First

| p3 | p2 | Statistic Data | Unit |
|--------------------------|-----------|--------------------------------|-------------|
| 0 (Present) | 0 | Present Motor History | m |
| | 1 | Present TPH History | m |
| | 2 | Present Auto-Cutter History | - |
| | 3 | Present Cover-Open History | - |
| | 4 | Present Feed Button History | - |
| | 5 | Present Pause Button History | - |
| 1 (Permanent) | 0 | Permanent Motor History | m |
| | 1 | Permanent TPH History | m |
| | 2 | Permanent Auto-Cutter History | - |
| | 3 | Permanent Cover-Open History | - |
| | 4 | Permanent Feed Button History | - |
| | 5 | Permanent Pause Button History | - |

3. Programming Example

3-1 Example) T_resident

```
SS3          // Set Speed to 5 ips
SD20         // Set Density level to 20
SW800        // Set Label Width 800
SOT          // Set Printing Orientation from Top to Bottom
T26,20,0,1,1,0,0,N,N,'Font - 6 pt'
T26,49,1,1,1,0,0,N,N,'Font - 8 pt'
T26,81,2,1,1,0,0,N,N,'Font - 10 pt'
T26,117,3,1,1,0,0,N,N,'Font - 12 pt'
T26,156,4,1,1,0,0,R,N,'Font - 15 pt'
T26,200,5,1,1,0,0,N,N,'Font - 20 pt'
T26,252,6,1,1,0,0,N,N,'Font - 30 pt'
P1
```

Result

Font – 6 pt
Font – 8 pt
Font – 10 pt
Font – 12 pt
Font – 15 pt


Font – 20 pt

Font – 30 pt

3-2 Example) T_Rotate4

```
SS3
SW832
T300,500,4,1,1,0,0,N,N,'ABCDEFG'
T300,500,4,1,1,0,1,N,N,'ABCDEFG'
T300,500,4,1,1,0,2,N,N,'ABCDEFG'
T300,500,4,1,1,0,3,N,N,'ABCDEFG'
P1
```

Result



ABCDEG
ABCDEG
ABCDEG
ABCDEG
ABCDEG
ABCDEG
ABCDEG

3-3 Example) V_resident

```
SS3                                // Set speed to 5 ips
SD20                               // Set density to 20
SW800                               // Set label width to 800
SOT                                 // Set printing direction to from top to bottom
V50,100,U,25,25,+1,N,N,N,0,L,0,'Vector Font Test'
V50,200,U,35,35,-1,N,N,N,0,L,0,'Vector Font Test'
V50,300,U,35,35,+1,B,R,I,0,L,0,'Vector Font Test '
V50,400,U,45,25,+1,N,N,N,0,L,0,'Vector Font Test'
V50,500,U,25,45,+1,N,N,N,0,L,0,'Vector Font Test'
V50,700,U,65,65,+1,N,N,N,0,L,0,'ABCDEFGHIJKLMNO'
V50,900,U,65,65,+1,N,N,N,0,L,0,'abcdefghijklmno'
P1
```


Result



3-4 Example) V_Rotate4

```
SS3
SW832
V400,500,U,45,40,+1,N,N,N,0,L,0,'VECTOR FONT'
V400,500,U,45,40,+1,N,N,N,1,L,0,'VECTOR FONT'
V400,500,U,45,40,+1,N,N,N,2,L,0,'VECTOR FONT'
V400,500,U,45,40,+1,N,N,N,3,L,0,'VECTOR FONT'
P1
```



Result



3-5 Example) Code39

```
SM10,0  
B178,196,0,2,6,100,0,0'1234567890' // Caution : The position is not (178,196)  
                                but (78,196).  
B150,468,0,4,10,200,0,0'1234567890'  
P1
```

Result




3-6 Example) BD1

```
SS3                      // Set Speed to 5 ips
SD20                     // Set Density level to 20
SW800                    // Set Label Width to 800

BD50,50,750,500,B,20
T100,150,5,1,1,0,0,N,N,'Normal Mode'
T100,300,5,1,1,0,0,R,N,'Reverse Mode'

SOT
P1
```

Result



3-7 Example) BD3


```
SS3                                // Set Printing Speed to 5 ips
SD20                               // Set Printing Density level to 20
SW800                               // Set Label Width to 800

BD50,100,400,150,O                // Draw a block in Overwriting Mode
BD50,200,400,250,O
BD50,300,400,350,O
BD100,50,150,400,E               // Draw a block in Exclusive OR mode
BD200,50,250,400,E
BD300,50,350,400,E
BD500,200,700,400,O
BD510,210,670,370,D              // Draw a block in Delete mode, namely Erase block
                                   area

BD100,600,350,1000,O
T50,700,5,1,1,0,0,N,N,'NORMAL'   // Write Text data on image buffer
T50,800,5,1,1,0,0,N,N,'NORMAL'
BD110,780,340,900,E
T500,700,5,1,1,0,0,n,N,'TEST'
BD480,680,700,800,E

SOT                                // Set Printing Orientation from Top to Bottom
P1                                 // Start Printing
```

Result



3-8 Example) BD4


SW800

SM10,0

BD100,300,550,330,O // Overwrite mode
BD200,200,250,430,O // Overwrite mode
BD400,200,450,430,E // Exclusive OR mode

P1


Result



3-9 Example) BD5

```
CB  
SW800  
SM10,0  
BD100,300,300,500,O  
BD400,300,700,500,B,30           // Box mode, additional parameter follows P1
```

Result



3-10 Example) Slope

CB
SS3
SD20
SW8000

BD100,300,300,800,**S,100** // Slope mode, additional parameter
follows BD600,300,400,800,**S,100**

P1

Result



3-11 Example) SW&SL

CB
SS3
SD20

SW800 // Set Label Width to 800
SL300,10,C // Continuous type
BD0,0,800,300,B,10
T30,40,4,1,1,0,0,N,N,'SW=800, SL=300, Continuous'
P1

SW600
SL500,10,C
BD0,0,600,500,B,10
T30,40,4,1,1,0,0,N,N,'SW=600, SL=500'
T30,100,4,1,1,0,0,N,N,'Continuous'
P1

SW400
SL800,10,C
BD0,0,400,800,B,10
T30,40,4,1,1,0,0,N,N,'SW=400'
T30,90,4,1,1,0,0,N,N,'SL=800'
T30,140,4,1,1,0,0,N,N,'Continuous'
P1

Result

SW = 800, SL=300, Continuous

**SW = 600, SL=500,
Continuous**

**SW= 400,
SL = 800,
Continuous**

3-12 Example) TEST00_TS

```
TD'Test00'                                // Template Delete
TS' Test00'                                 // Start Template Store

SV00,15,N,'Manufacturer :'                // Declare variable V00, field size:15, No justification
SV01,15,R,'Model Name :'                  // Declare variable V01, field size:15, Right justification

T50,100,3,1,1,0,0,N,N,'Manufacturer :V00 // Print variable V00 with some text string
T50,150,3,1,1,0,0,N,N,'Model Name :V01 // Print variable V01 with some text string
T50,300,3,1,1,0,0,N,N,V00                 // Print variable V00 only
T50,350,3,1,1,0,0,N,N,V01                 // Print variable V01 only

TE                                         // End Template Store

TI                                         // Print and show all templates in memory
```

Result

Templates Information

=====

- | | | |
|----------|---|---------------------|
| 1. Test1 | ← | Stored in past time |
| 2. Test0 | ← | Stored in this time |

Available template memory : 5.3Kbyte

3-13 Example) TEST00_TR

```
TR'Test00'          // Recall Stored template 'Test00'  
  
?                  // To get contents for variables used in 'Test00'  
BIXOLON           // Content for V00  
XT5-40            // Content for V01  
  
P1                // Print
```

Result

| | | |
|------------------------|----------|---------------------|
| Manufacturer : BIXOLON | ← | No Justification |
| Model Name : | XT5-40 ← | Right Justification |
| BIXOLON | ← | No Justification |
| XT5-40 | ← | Right Justification |

3-14 Example) TEST04_TS

```
TS'Test04'                                // Start Template Store

CB                                         // Clear Image Buffer
SS3                                        // Set Speed to 5 ips
SD20                                       // Set Density level 20
SW800                                       // Set Label Width to 800
SOT                                         // Set Printing Orientation from Top to Bottom(Default)

SV00,15,L,'prompt'                         // Declare variable V00, field size:15, Left justification
SV01,15,R,'prompt'                          // Declare variable V01, field size:15, Right justification
SV02,15,C,'prompt'                          // Declare variable V02, field size:15, Center
                                             justification
SV03,15,N,'prompt'                          // Declare variable V03, field size:15, No justification
SV04,15,L,'prompt'                          // Declare variable V04, field size:15, Left justification
SV05,15,R,'prompt'                          // Declare variable V05, field size:15, Right justification
SV06,15,C,'prompt'                          // Declare variable V06, field size:15, Center
                                             justification
SV07,15,N,'prompt'                          // Declare variable V07, field size:15, No justification

T26,50,4,1,1,0,0,R,N,V00                   // Print variable only
T26,100,4,1,1,0,0,R,N,V01
T26,150,4,1,1,0,0,R,N,V02
T26,200,4,1,1,0,0,R,N,V03
T26,250,4,1,1,0,0,R,N,'BIXOLON :V04    // Print variable with fixed text data
T26,300,4,1,1,0,0,R,N,'BIXOLON :V05
T26,350,4,1,1,0,0,R,N,'BIXOLON :V06
T26,400,4,1,1,0,0,R,N,'BIXOLON :V07

TE                                         // End Template Store
```

3-15 Example) TEST04_TR

```
TR'Test04'      // Recall Template  
  
?                // Start Get values  
                 for variables  
A                // data for variable V00  
B                // data for variable V00  
C                .  
D                .  
E                .  
F                .  
G                .  
H                // data for variable V07  
  
P1               // Start Printing
```

A
B
C
D
BIXOLON : E
BIXOLON : F
BIXOLON : G
BIXOLON : H

3-16 Example) IR1

```
IR130,400,'BIXOLON'          // Recall stored image data  
P1                           // Printing
```

!!! Use the PCXDown utility when you download the pcx image file to printer memory. Refer to IS command.

Result

The BIXOLON logo, featuring the word "BIXOLON" in a bold, sans-serif font with a registered trademark symbol (®) at the end, all contained within a rectangular border.

3-17 Example) TEST10_TS

```
TS'Test10'          // Start Template Store

CB                  // Clear Image Buffer
SS3                // Set Speed to 5 ips
SD20               // Set Density to 20
SW800              // Set Label Width to 800
SOT                // Set Printing Orientation from Top to bottom

SV00,15,C,'prompt' // Declare Variable 00
SV01,15,N,'prompt' // Declare Variable 01
SV02,10,N,'prompt' // Declare Variable 02

T130,250,5,1,1,0,0,R,N,V00 // Print Content of V00
T250,600,5,1,1,0,0,N,N,V01 // Print Content of V01
IR130,400,V02           // Use V02 as Image Name

TE                  // End Template Store
```

3-18 Example) TEST10_TR

(File location : CD\Testfile\Template\Test10\TEST10_TR.txt)

```
TR'Test10'          // Recall Template

?                  // Start Get data for variables
BIXOLON           // data for V00
XT5-40             // data for V01
BIXOLON           // data for V02(Image Name)

P1                // Start Printing
```

BIXOLON

BIXOLON®

XT5-40

3-19 Example) TEST11_TS

```
TS'Test11'          // Start Template Store

CB                  // Clear Image Buffer
SS3                // Set Printing Speed to 5 ips
SD20               // Set Density to 20
SW800              // Set Label Width to 800
SOT                // Set Printing Orientation from Top to Bottom
SC0,4,L,+1,'COUNTER1' // Declare Counter 0, Field=4, Step:+1,Left Justi.
SC1,4,N,-1,'COUNTER2' // Declare Counter 1, Field=4, Step: -1,No Justi.
T50,50,4,1,1,0,0,N,N,'Serial Number : 'C0 // Print Counter 0
T50,150,4,1,1,0,0,R,N,'Serial Number : 'C1 // Print Counter 1
TE                 // End of Template Store
```

3-20 Example) TEST11_TR

```
TR'Test11'          // Recall Template

?                  // Start Get values for
                  // variables
0001              // data for Counter 0
9999              // data for Counter 1
P3,1

?
```

Serial Number : 0001

Serial Number : 9999

Serial Number : 0002

Serial Number : 9998

Serial Number : 0003

Serial Number : 9997

Serial Number : 9999

Serial Number : 0001

Serial Number : 0000

Serial Number : 0000

Serial Number : 0001

Serial Number : 9999

3-21 Example) SAMPLE LABEL

```
SM10,20
SW832
SC0,3,N,+1,'prompt'
T16,20,1,0,0,0,0,N,N,'SHIPPERS INTERNATIONAL'
T16,48,1,0,0,0,0,N,N,'(123)456-7890'
T16,76,1,0,0,0,0,N,N,'5TH FLOOR'
T16,104,1,0,0,0,0,N,N,'1550 W ANYWHERESTREET'
T16,132,1,0,0,0,0,N,N,'PHEONIX AZ 85027-3129'
T474,16,3,0,0,0,0,N,B,'12LBS'
T658,16,3,0,0,0,0,N,B,'1 OF 2'
T508,56,1,0,0,0,0,N,N,'DWT:15 LBS'
T508,84,1,0,0,0,0,N,N,'AH'
T24,180,3,0,0,0,0,N,B,'SHIP'
T32,224,3,0,0,0,0,N,B,'TO'
T124,184,3,0,0,0,0,N,N,'JOHN SMITH'
T124,216,3,0,0,0,0,N,N,'(987)654-3210'
T124,248,3,0,0,0,0,N,N,'ABC COMPANY'
T124,280,3,0,0,0,0,N,N,'BUILDING 3 FLOOR4'
T124,312,3,0,0,0,0,N,N,'123 MAIN STREET'
T124,356,4,0,0,0,0,N,B,'SALT LAKE CITY UT 84170-6672'
T270,408,6,0,0,0,0,N,B,'UT 841 9-06'
T16,648,5,0,0,0,0,N,B,'UPS NEXT DAY AIR'
T16,712,2,0,0,0,0,N,N,'TRACKING# : 1Z 123 45E 24 1234 5677'
T16,1016,1,0,0,0,0,N,N,'BILLING: P/P'
T16,1040,1,0,0,0,0,N,N,'SIGNATURE REQUIRED'
T16,1064,1,0,0,0,0,N,N,'HAZADOUS MATERIAL'
T640,646,5,2,2,0,0,N,N,'1'
B1368,496,1,2,6,100,0,0,'1234567890'
B160,768,1,4,10,200,0,0,'1234567890'
BD30,396,816,400,O
BD30,624,816,634,O
BD30,746,816,750,O
BD30,976,816,986,O
BD256,398,260,624,O
B216,400,M,2,'999,840,06810,7317, THIS IS A TEST OF LABEL PRINTER SRP-770III. MODE 2
ENCODING. THIS IS AN 84 CHAR.'
P1
```

Result



Revision History